Probabilistic Analysis and Randomized Algorithms



Probability Basics (Ap. C)

- Counting
  - Permutations, k-permutations
  - k-combination, binomial coefficients
- Probability
  - Axioms, discrete distribution
  - Conditional probability
  - Independent events
  - Bayes theorem $\Pr\{A \mid B\}=\Pr\{A\}\Pr\{B \mid A\}/\Pr\{B\}$



Probability Basics (Ap. C)

- Discrete random variables
  - function from sample space S to real numbers
  - probability density function $Pr\{X=x\}=\sum_{s\in S:X(s)=x} xPr\{s\}$
  - expected value $E[X]=\sum_x Pr\{X=x\}$
- Bernoulli trial
- Geometric distribution
- Binomial distribution



What is it about?

- Worst case analysis: wort cost or running time of an algorithm.
- Probabilistic analysis: compute the average case in terms of cost or running time.
- Randomized algorithms: algorithms that have a randomized decision.



Hiring Problem Example

- The problem: hire new office assistant and fire the old (worse) one.
- Cost of interviewing and hiring $O(nc_i+mc_h)$
- Worst case $O(nc_h)$ (focus on hiring)
- Probabilistic analysis:
  - $E[X_i]=\Pr\{\text{candiate } i \text{ hired}\}=1/i$
  - $E[X]=\ln(n)+O(1)$
  - expected cost is $O(c_h \ln(n))$



Randomized Algorithms

- Distinction between probabilistic analysis of an algorithm, knowing its *input distribution*, and analysis of randomized algorithms for *any input*.
- Randomized hire algorithm: permute list of candidates:
  - no particular input will show the worst-case
  - every run is different, although the final result is the same



Permuting Arrays

- A way to randomize inputs
- Permute-by-sorting
  - assign random priorities and sort
  - uniform random permutation
- Randomize-in-place
  - swap elements randomly
  - uniform random permutation